



Product Specification 7108

Taconic 7108 is a standard 10 mil PTFE coated fiberglass fabric. This material exhibits release properties, heat resistance, and chemical resistance. Common applications include heat sealing/poly packaging, tray lining, composite release liners, food processing (platen covering), gaskets and seals, uPVC window welding, and a variety of aerospace applications. Maximum width is 62" wide.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PTFE		
% Coating	%	59	+/- 2%	
Total Coated Weight	lbs/yd2	0.92	+/- 5%	ASTM D4969
Nominal Thickness	inch	0.009		ASTM D4969
Coating Adhesion Strength	lbs/in	3.75	Typical	ASTM D751
		2.3	Minimum	
Dielectric Breakdown	volts/mil	600	Typical	ASTM D149 Method A
		500	Minimum	
Tensile Strength	lbf/in	285	Typical Warp	ASTM D902
		220	Minimum Warp	
		185	Typical Fill	
		105	Minimum Fill	
Tear Strength	lbs	12	Typical Warp	ASTM D5587
		5.2	Minimum Warp	
		7	Typical Fill	
		1.8	Minimum Fill	
Operating Temperature	°Fahrenheit	-100° to +500°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

This product is suitable for direct and repeated use in a food contact application when used in accordance with the product specifications.



Please contact us for samples or a quotation

Taconic Headquarters
 Petersburg, NY
www.4taconic.com
info@4taconic.com

Western US, Mexico & Central America
 La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
 Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
 or email info@taconic-ipd.com

