



Product Specification 6115-03

Taconic 6115-03 is a skived virgin PTFE film tape complete with silicone adhesive. This tape is highly conformable and has a very low coefficient of friction. The non-stick PTFE film surface is ideal for wear stripping, lining, and for chemical resistance. With silicone adhesive, this tape is suited for applications in elevated temperatures. This tape is available with a dimpled yellow release liner. Maximum width is 38" wide.

| Product Properties | Units | Value | Tolerance | Test Method |
|---------------------------|-------------|-----------------------|-----------|------------------------|
| Adhesive Type | | SILICONE | | |
| Substrate Type | | PTFE FILM | | |
| Total Weight of Substrate | | N/A | | |
| % Coating of Substrate | | N/A | | |
| Substrate Thickness | inch | 0.003 | | ASTM D3652 |
| Adhesive Thickness | inch | 0.002 | | ASTM D3652 |
| Total Product Thickness | inch | 0.005 | | ASTM D3652 |
| Adhesive Strength | ozs | 37 | Typical | ASTM D3330 METHOD A |
| | | 30 | Minimum | |
| Adhesive Shelf Life | Months | 12 | From DOM | |
| Operating Temperature | °Fahrenheit | -100° to +500° | | |

Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/- 10%

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



#3083

Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com

