



Product Specification **6635-20**

Taconic 6635-20 is a double layer combination tape built from a layer of silicone coated fiberglass and a layer of aluminum foil with glass complete with high performance silicone adhesive. The tape is designed to withstand high abrasion while providing exceptional edge definition. This tape comes with a yellow dimpled PVC release liner. Maximum width is 38" wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		SILICONE		
Substrate Type		LSR E-GLASS		
Total Weight of Substrate		N/A		
% Coating of Substrate		N/A		
Substrate Thickness		N/A		ASTM D3652
Adhesive Thickness	inch	0.003		ASTM D3652
Total Product Thickness	inch	0.019		ASTM D3652
Adhesive Strength	ozs	20	Typical	ASTM D3330 METHOD A
		10	Minimum	
Adhesive Shelf Life	Months	12	From DOM	
Operating Temperature	°Fahrenheit	-100° to +500°		

Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/- 10%

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com

