



Product Specification **7102W**

Taconic's 7102 is a glass fibre product coated with silicone, whose high friction and release properties offer excellent value and performance across a wide variety of industrial applications. With its abrasion and flex resistant surface, excellent chemical resistance, superior dielectric and release properties, 7102 is used as a high friction conveyor belt and electrical insulator in many industries and also as a curtain material in packaging applications. Standard width of 7102 is 1000mm, with availability in red or white.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		SILICONE RUBBER		
% Coating	%	68	+/-2%	
Total Coated Weight	g/sqm	340	+/-5%	
Nominal Thickness	microns	235		
Tensile Strength	N/5cm	1500	Typical Warp	ISO 1421
		1000	Minimum Warp	
		900	Typical weft	
		650	Minimum weft	
Colour		WHITE		
Operating Temperature	°Celsius	-73° to +230°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com



Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com



Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com



For queries in North America please visit www.4taconic.com or email info@4taconic.com