



Product Specification 7152

Taconic's 7152 is a silicone coated glass fibre product with high friction and release properties which offers excellent value and performance across a wide variety of industrial applications. With its abrasion and flex resistant surface, excellent chemical resistance, superior dielectric and release properties, 7152 is used as a high friction conveyor belt and electrical insulator in many industries and also as a curtain material in packaging applications. Standard width of 7152 is 1000mm & 1200mm, with colour availability in red or white.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		SILICONE RUBBER		
% Coating	%	62		ISO 2286-2
Total Coated Weight	g/m ²	540	+/- 5%	ISO 2286-2
Nominal Thickness	microns	380		ISO 2286-3
Tensile Strength	N/5cm	2000	Typical Warp	ISO 1421
		1500	Minimum Warp	
		N/A	Typical weft	
		N/A	Minimum weft	
Colour		White		
Rubber Hardness	Shore A	75		BS ISO 7619-1
Operating Temperature	°Celsius	-73° to +230°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com



Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com



Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com



For queries in North America please visit www.4taconic.com or email info@4taconic.com