

Product Specification

Taconic's 7422 is a silicone coated glass fibre product with high friction and release properties which offers excellent value and performance across a wide variety of industrial applications. With its abrasion and flex resistant surface, excellent chemical resistance, superior dielectric and release properties, 7422 is used as a high friction conveyor belt and electrical insulator in many industries and also as a curtain material in packaging applications. Standard width of 7422 is 1000mm, with colour availability in red or white.

7422W

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		SILICONE RUBBER		
% Coating	%	62	+/-2%	
Total Coated Weight	g/sqm	1420	+/-5%	
Nominal Thickness	microns	1000		
Tensile Strength	N/5cm	6000	Typical Warp	ISO 1421
		4000	Minimum Warp	
		5000	Typical weft	
		3600	Minimum weft	
Colour		WHITE		
Operating Temperature	°Celsius	-73° to +230°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic International Ltd Ireland <u>www.taconic-ipd.com</u> <u>info@taconic-ipd.com</u>



Please contact us for samples or a quotation

Taconic France France www.taconic-ipd.fr info@taconic-ipd.fr Taconic International Ltd Germany <u>www.taconic.de</u>

Wildcat Taconic United Kingdom <u>www.taconic-ipd.com</u> info@wildcat-taconic.com



Rev: 04/21 - 001

 info@taconic-ipd.fr
 info@taconic.de
 info@wildcat-taconic.com

 For queries in North America please visit www.4taconic.com
 or email info@4taconic.com