



Product Specification 10-69-128

Taconic 10-69-128 is a textured 8 mil PTFE coated fiberglass fabric. This material exhibits release properties, heat resistance, and chemical resistance. The unique surface texture provides a visibly embossed pattern in poly films during the heat sealing process. Max width is 44" wide.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PTFE		
% Coating	%	46	+/- 2%	
Total Coated Weight	lbs/yd2	0.7	+/- 5%	ASTM D4969
Nominal Thickness	inch	0.0085		ASTM D4969
Coating Adhesion Strength	lbs/in	6	Typical	ASTM D751
		4	Minimum	
Dielectric Breakdown	volts/mil	280	Typical	ASTM D149 Method A
		160	Minimum	
Tensile Strength	lbf/in	230	Typical Warp	ASTM D902
		190	Minimum Warp	
		185	Typical Fill	
		140	Minimum Fill	
Tear Strength	lbs	18	Typical Warp	ASTM D5587
		10	Minimum Warp	
		12	Typical Fill	
		6	Minimum Fill	
Operating Temperature	°Fahrenheit	-100° to +500°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic Headquarters
 Petersburg, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
 La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
 Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
 or email info@taconic-ipd.com

