



Product Specification 7063AS

Taconic 7063AS is a 6 mil Black anti-static PTFE coated fiberglass fabric. This material exhibits release properties, heat resistance, UV resistance, chemical resistance, and allows for good heat transfer. The material resists a buildup of static electricity. This fabric is commonly used in electronics and semiconductor applications or for situations where static electricity is a problem. Maximum width is 38" wide.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PIGMENTED PTFE		
% Coating	%	65	+/- 2%	
Total Coated Weight	lbs/yd2	0.55	+/- 5%	ASTM D4969
Nominal Thickness	inch	0.0055		ASTM D4969
Coating Adhesion Strength	lbs/in	3.25	Typical	ASTM D751
		2	Minimum	
Tensile Strength	lbf/in	150	Typical Warp	ASTM D902
		100	Minimum Warp	
		150	Typical Fill	
		100	Minimum Fill	
Tear Strength	lbs	6.25	Typical Warp	ASTM D5587
		3.5	Minimum Warp	
		6.25	Typical Fill	
		3.5	Minimum Fill	
Surface Resistivity	KOhm/sq	100		
Operating Temperature	°Fahrenheit	-100° to +500°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic Headquarters
 Petersburg, NY
www.4taconic.com
info@4taconic.com

Western US, Mexico & Central America
 La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
 Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
 or email info@taconic-ipd.com

