



Product Specification 7115

Taconic 7115 is a 11 mil porous PTFE coated fiberglass fabric. This material is referred to as a bleeder cloth. This fabric is commonly used as a release sheet in the production of composite materials. The construction of the fabric allows for release properties and “bleed through” where required. Maximum width is 104” wide.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PTFE		
% Coating	%	29	+/- 2%	
Total Coated Weight	lbs/yd2	0.77	+/- 5%	ASTM D4969
Nominal Thickness	inch	0.013		ASTM D4969
Coating Adhesion Strength	lbs/in	7	Typical	ASTM D751
		4.5	Minimum	
Dielectric Breakdown	volts/mil	10	Typical	ASTM D149 Method A
		10	Minimum	
Tensile Strength	lbf/in	250	Typical Warp	ASTM D902
		150	Minimum Warp	
		215	Typical Fill	
		150	Minimum Fill	
Tear Strength	lbs	25	Typical Warp	ASTM D5587
		15	Minimum Warp	
		15	Typical Fill	
		7	Minimum Fill	
Operating Temperature	°Fahrenheit	-100° to +500°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

This product is suitable for direct and repeated use in a food contact application when used in accordance with the product specifications.



#3083

Taconic Headquarters
 Petersburg, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
 La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
 Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
 or email info@taconic-ipd.com

