



Product Specification 7143

Taconic 7143 is a 14 mil Black pigmented PTFE coated fiberglass fabric. This material exhibits release properties, heat resistance, UV resistance, and chemical resistance. The black color also helps retain heat. Common applications include plastic packaging, tray lining, gaskets, and seals. Maximum width is 104" wide.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PIGMENTED PTFE		
% Coating	%	60	+/- 2%	
Total Coated Weight	lbs/yd2	1.36	+/- 5%	ASTM D4969
Nominal Thickness	inch	0.0148		ASTM D4969
Coating Adhesion Strength	lbs/in	10	Typical	ASTM D751
		6.5	Minimum	
Dielectric Breakdown	volts/mil	140	Typical	ASTM D149 Method A
		80	Minimum	
Tensile Strength	lbf/in	410	Typical Warp	ASTM D902
		350	Minimum Warp	
		320	Typical Fill	
		230	Minimum Fill	
Tear Strength	lbs	10.4	Typical Warp	- ASTM D5587
		8.5	Minimum Warp	
		7.8	Typical Fill	
		5.5	Minimum Fill	
Operating Temperature	°Fahrenheit	-100° to +500°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

This product is suitable for direct and repeated use in a food contact application when used in accordance with the product specifications.



www.4taconic.com info@4taconic.com





Please contact us for samples or a quotation

Western US, Mexico & Central America

La Verne, CA www.4taconic.com info@4taconic.com

For queries in Europe please visit www.taconic-ipd.com or email info@taconic-ipd.com

Canada Mississauga, CAN www.4taconic.com info@4taconic.com





Rev: 04/24 - 005